

TECHNICAL SPECIFICATIONS



FLOOR MATS

Technical Specifications	Standard	Mats
Warranty	–	3 years*
 Composition	–	95%PVC + 5%PES
 Total Weight	ISO 8543	2700 g/m ² 12mm thickness 3300 g/m ² 15mm thickness 3600 g/m ² 20mm thickness
 Thickness	ISO 1765	6 – 20 mm
 Light Fastness	EN ISO 105-B02	≥ 6
 Dimensional Stability	EN 986 ISO 2551	≤ 0.25%
 Castor Chair Suitability	EN 985:2002	Intensive Use
 Sound Insulation	ISO 10140	12 dB
 Thermal Resistance	ISO 8302	Suitable for Underfloor Heating
 Static Electricity	ISO 6356	< 2KV
 Slip Resistance	EN13893	≥ 0,3 0,85 R9 65
 Reaction to Fire	EN 13501-1	Bfl-s1
 CE Certificate	EN 14041	NO.EC.1282. OA140305.AYD0738
 Level of Use	EN 1307:2014	Class 33 Heavy Commercial Use

All specifications are based on average values and may deviate. The values are for guidance and are not contractual. Subject to technical modifications.

The straight weft is not an inherent condition. Weaving technology features colour effects because of light, making it an exclusive and unique product. Also bicolour yarns create a randomly harmonious effect. These effects are no ground for claims.

CERTIFICATIONS



ECO BEAUTY™ China

Bamboo Industrial Zone, Huzhou, Zhejiang Province, China

China Sales Direct: +86-572-5705325

Export Sales Direct: +86-572-5705325

China Fax: +86-572-5216088

Export Fax: +86-572-5216088

Tel.: +86-198 8317 9548

Email: Sam@theflooring.pro

Website: <https://theflooring.pro>

ECO BEAUTY™
Premium Woven Vinyl Mats